

1. Product Type and Definition

OBEX CORTEX O200FR Class A2 Interface Sealing Membrane

2. Name and Contact Address of Supplier

OBEX Protection Ltd, Unit 5 St. Modwen Park, Norton Road, Broomhall, Worcester, WR5 2QR

3. Intended Use

EN 13984:2013 Flexible Sheets for Waterproofing – Plastic and Rubber Vapour Control Layers – Type A

4. Systems of Assessment and Verification of Constancy of Performance (AVCP)

System 3

5. Notified Body

System Laboratories UK – Approved Body 8514
Shirley Technologies / BTTG – Approved Body 0338

6. Declared Performance

Harmonised Standard	EN 13984:2013	
Reaction to Fire	EN 13501-1	A2-s1,d0
Water Tightness	EN 1928 (A)	Pass – 2kPa for 24 hours
Tensile Strength (MD)	EN 12311-2	7767 N / 50mm
Tensile Strength (CD)	EN 12311-2	3973 N / 50mm
Tear Strength (MD)	EN 12310-1	519 N
Tear Strength (CD)	EN 12310-1	436 N
Artificial Ageing by UV & Heat	EN 1297 & EN 1296	
Tensile Strength (MD)	EN 12311-2	7699 N / 50mm
Tensile Strength (CD)	EN 12311-2	3813 N / 50mm
Alkali Ageing	EN 1847 (Milk of Lime)	
Tensile Strength (MD)	EN 12311-2	7270 N / 50mm
Tensile Strength (CD)	EN 12311-2	3659 N / 50mm
Water Tightness	EN 1928 (A)	Pass – 2kPa for 24 hours

The performance of the product identified in section 1 is in conformity with the declared performance in section 6. This Declaration of Performance (DoP) is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in section 2.

Signed for and on behalf of the manufacturer by:



Callum Doouss

10.09.2024