

1. Product Type and Definition

OBEX CORTEX 0530FR Class B Vapour Control Layer

2. Name and Contact Address of Supplier

OBEX Protection Ltd, Unit 5 St. Modwen Park, Norton Road, Broomhall, Worcester, WR5 2QR

3. Intended Use

EN 13984:2013 Flexible Sheets for Waterproofing – Plastic and rubber vapour control layers

4. Systems of Assessment and Verification of Constancy of Performance (AVCP)

System 3

5. Notified Body

Lucideon – Approved Body 1289

System Laboratories – Approved Body 8514

6. Declared Performance

Harmonised Standard	EN 13984:2013	
Reaction to Fire	EN 13501-1	B-s1,d0
Water Tightness	EN 1928 (A)	Pass – 2kPa for 24 hours
Tensile Strength (MD)	EN 12311-2	160 N / 50mm
Tensile Strength (CD)	EN 12311-2	155 N / 50mm
Tear Strength	EN 12310-1	142 N
Water Vapour Transmission	EN 1931	100m
Artificial Ageing by UV & Heat	EN 1297 & EN 1296	
Water Tightness	EN 1928	Pass – 2kPa for 24 hours
Tensile Strength (MD)	EN 12311-2	132 N / 50mm
Tensile Strength (CD)	EN 12311-2	144 N / 50mm

The performance of the product identified in section 1 is in conformity with the declared performance in section 6. This Declaration of Performance (DoP) is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in section 2.

Signed for and on behalf of the manufacturer by:



Callum Doouss

10.09.2024

