

## Product Description

OBEX CORTEX 0210FR Class A Paste Adhesive is a high-quality, moisture-curing adhesive, used for bonding and sealing Interface Sealing Membranes. Developed for applications where products with a high fire classification are required.

## Product Specifications

Colour	Black
Pack	12 x 600ml foil
Shelf life	12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

## Product Applications

» For bonding and sealing of membranes onto other building substrates. Porous surfaces should be primed with OBEX CORTEX 0787FR Class B Primer. Primer is not required for non-porous substrates.

## Technical Data

Fire Classification	A2-s1, d0
Chemical Base	Oxime
Consistency	Stable Paste
Curing System	Moisture Curing
Curing Time	2mm/24 hours (23°C, %50 R.H)
Shore A	20, DIN 53 505 (N/mm <sup>2</sup> )
Density	1.40 ± 0.03gr/cm <sup>3</sup>
Elongation	458%
Maximum Allowed Distortion	23%
Temperature Resistance	-50°C to 120°C
Tensile Strength	1.0 MPa
Application Temperature	5°C to 40°C

## Application Method

- » Applied using a manual or pneumatic caulking gun. Surfaces to be clean, dry and free of dust, grease and oils etc.
- » Clean with OBEX CORTEX 0795 Cleaning Wash immediately after use.
- » Repair with the same material.


## Associated Products

- » OBEX CORTEX 0200FR Class A Interface Sealing Membrane
- » OBEX CORTEX 0787FR Class B Primer

## Additional Important Information

- » The adhesive will stain natural stones like marble and granite.
- » It is the responsibility of the user to test for compatibility.
- » Consult the OBEX Technical Team with any queries.

### Installation Guide\*



Scan the QR code for the Installation Guide, to ensure an accurate and compliant install.

Alternatively follow this link:  
[obexuk.qrd.by/0200fr-install](https://obexuk.qrd.by/0200fr-install)

\*Install Guide for 0200FR, which 0210FR is used with