

1. Product Type and Definition

OBEX CORTEX 0230FR Class A2 Vapour Control Layer

2. Name and Contact Address of Supplier

OBEX Protection Ltd, Unit 5 St. Modwen Park, Norton Road, Broomhall, Worcester, WR5 2QR

3. Intended Use

EN 13984:2013 Flexible Sheets for Waterproofing – Plastic and rubber vapour control layers

4. Systems of Assessment and Verification of Constancy of Performance (AVCP)

System 3

5. Notified Body

System Laboratories – Approved Body 8514

Shirley Technologies / BTTG – Approved Body 0338

6. Declared Performance

Harmonised Standard	EN 13984:2013	
Reaction to Fire	EN 13501-1	A2-s1,d0
Water Tightness	EN 1928 (A)	Pass – 2kPa for 24 hours
Tensile Strength (MD)	EN 12311-2	1362 N / 50mm
Tensile Strength (CD)	EN 12311-2	1349 N / 50mm
Tear Strength (MD)	EN 12310-1	150 N
Tear Strength (CD)	EN 12310-1	150 N
Water Vapour Transmission	EN 1931	2575.35m
Artificial Ageing by Heat	EN 1296	
Water Vapour Transmission	EN 1931	2575.35m

0230FR Vapour Control Layer Class A2**Declaration of Performance**

DoP: 0230FR-230622

Version: 02.01.02

Updated: 12.08.25

The performance of the product identified in section 1 is in conformity with the declared performance in section 6. This Declaration of Performance (DoP) is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in section 2.

Signed for and on behalf of the manufacturer by:

**Callum Doouss**

12.08.25