

Product Description

The screws have a self-countersinking head for a secure and flush finish, and a self-drilling point with a self-tapping thread. The screws have an exterior grade coating for superior corrosion resistance in damp or corrosive environments, compared to standard fasteners.

Product Applications

- » **Drill Point: For fixing OBEX CORTEX 0270FR Cement Board to steel framing systems (max. 3.0mm)**

Product Specifications (Steel Fixings)

Point Type	Drill Point
Diameter	4.2mm
Length	32mm or 42mm
Head Diameter	10mm
Effective Thread Length	19mm or 29mm
Drill Point Diameter	3.46mm
Drill Point Length	5.11mm

Technical Data

	Drill Point (Steel Fixings)
Composition	Ceramic coated Carbon Steel
Rec. RPM	1,800-2,500
Drive recess Type	Phillips
Effective Thread Length	19mm or 29mm
Point Type	Drill Point/Self Drilling
Size	4.2mm x 32mm or 42mm
Head Ø	10mm
Finish	Exterior Plus

Associated Products

- » OBEX CORTEX 0270FR Cement Board
- » OBEX CORTEX 0280FR Board Sealant

Additional Important Information

- » Organic plating withstands 1,500 hours in salt spray test
- » Self-drilling point for fixing into light section steel
- » Ribs under the head for improved countersinking
- » 500no per pack