

#### 0500 EPDM Membrane

Technical Data Sheet

Version 01.01.01 Updated 06.10.23

### **Product Description**

OBEX CORTEX 0500 EPDM Membrane is used to create water and airtight seals across construction interfaces.

## **Product Specifications**

| Widths    | 50mm - 1500mm |
|-----------|---------------|
| Length    | 20m per roll  |
| Thickness | 0.5mm         |

# **Product Applications**

- » Water and airtight seals around windows, doors, and curtain-walling systems.
- » Water and airtight seals from sheathing board to concrete frame.
- » Top of parapet walls.
- » EPDM is not suitable for use on Relevant Buildings taller than 18m as specified in Reg 7. A fire-classified membrane is required - please speak to one of our advisors for further advice.

#### Technical Data

| Harmonised Standard                       | EN 13984        |                          |
|---|-----------------|--------------------------|
| 3rd Party Certification                   | BBA             | Certificate No. 17/5396  |
| Fire Classification                       | EN 13501-1      | E                        |
| Water Tightness                           | EN 1928         | Pass - 2kPa for 24 hours |
| Air Tightness                             | EN12114         | < 0.1m³ net leakage      |
| Tensile Strength (both directions)        | EN 12311-2      | ≥ 6 MPa                  |
| Resistance to tearing (nail shank)        | EN 12310-2      | ≥ 10 N                   |
| Water Vapour Permeability                 | EN 1931         | 50,000 mu                |
| Equivalent Air Layer Thickness (Sd Value) | EN 1931         | 25m                      |
| Vapour Resistance                         | EN 1931         | 125 MNs/g                |
| Elongation at break (both directions)     | EN 12311-2      | ≥ 250%                   |
| Vapour Resistivity                        | EN 1931         | 25,000 MNs/gm            |
| Durability Against Ageing                 | EN 1296/EN 1931 | Pass                     |
| Service Temperature (approx)              | -45°C to 130°C  |                          |





#### 0500 EPDM Membrane

# Technical Data Sheet

Version 01.01.01 Updated 06.10.23

#### **Associated Products**

- » OBEX CORTEX 1500 EPDM Membrane
- » OBEX CORTEX 1200 EPDM Membrane
- » OBEX CORTEX 1000 EPDM Membrane
- » OBEX CORTEX 0750 EPDM Membrane
- » OBEX CORTEX 0600 EPDM Membrane
- » OBEX CORTEX 0769 Paste Adhesive
- » OBEX CORTEX 0785 Primer
- » OBEX CORTEX Adhesive Backed EPDM Membrane
- » OBEX CORTEX 0751, 0752, 0753 EPDM Membrane with Butyl Strips
- » OBEX CORTEX 0761, 0762, 0763, 0764, 0768 EPDM Membrane with Gasket

#### Additional Important Information

- » All edges, joints and overlaps must be capped off with OBEX CORTEX 0769 Paste Adhesive.
- » Porous surfaces and sheathing boards must be primed with OBEX CORTEX 0785 Primer.
- » It is the responsibility of the user to carry out compatibility checks.
- » Consult the OBEX Technical Team with any queries.

#### **Installation Guide**



Scan the QR code for the Installation Guide, to ensure an accurate and compliant install.

Alternatively follow this link: obexuk.qrd.by/EPDM-install

