

Product Description

OBEX CORTEX EPDM Membrane With Butyl Strip(s) is used to create a water and airtight seal around windows, doors, and curtain walling on construction projects.

The EPDM can be supplied with a single butyl strip to one edge, or one strip to each edge on the same side, or one strip to each edge on opposite sides.

Product Specifications

Widths	50mm - 1500mm
Length	20m per roll
Thickness	0.75mm

Product Applications

- » Water and airtight seals around windows, doors, and curtain-walling systems.
- » Water and airtight seals from sheathing board to concrete frame.
- » Top of parapet walls.
- » EPDM is not suitable for use on Relevant Buildings taller than 18m as specified in Reg 7. A fire-classified membrane is required - please speak to one of our advisors for further advice.

Technical Data

Harmonised Standard	EN 13984	
3rd Party Certification	BBA	Certificate No. 17/5396
Fire Classification	EN 13501-1	E
Water Tightness	EN 1928	Pass - 2kPa for 24 hours
Air Tightness	EN12114	< 0.1m ³ net leakage
Tensile Strength (both directions)	EN 12311-2	≥ 7 MPa
Resistance to tearing (nail shank)	EN 12310-2	≥ 10 N
Water Vapour Permeability	EN 1931	50,000 mu
Equivalent Air Layer Thickness (Sd Value)	EN 1931	37.5m
Vapour Resistance	EN 1931	188 MNs/g
Elongation at break (both directions)	EN 12311-2	≥ 300%
Vapour Resistivity	EN 1931	25,000 MNs/gm
Durability Against Ageing	EN 1296/EN 1931	Pass
Service Temperature (approx)		-45°C to 130°C
Adhesion		>19 N/cm

Associated Products

- » OBEX CORTEX 1500 EPDM Membrane
- » OBEX CORTEX 1200 EPDM Membrane
- » OBEX CORTEX 1000 EPDM Membrane
- » OBEX CORTEX 0750 EPDM Membrane
- » OBEX CORTEX 0600 EPDM Membrane
- » OBEX CORTEX 0500 EPDM Membrane
- » OBEX CORTEX 0769 Paste Adhesive
- » OBEX CORTEX 0785 Primer
- » OBEX CORTEX 0860 Adhesive Backed EPDM Membrane
- » OBEX CORTEX 0761, 0762, 0763, 0764, 0768 EPDM Membrane with Gasket

Additional Important Information

- » All edges, joints and overlaps must be capped off with OBEX CORTEX 0769 Paste Adhesive.
- » Porous surfaces and sheathing boards must be primed with OBEX CORTEX 0785 Primer.
- » It is the responsibility of the user to carry out compatibility checks.
- » Consult the OBEX Technical Team with any queries.