

## Product Description

OBEX CORTEX 0823FR UV Façade Tape is a black, single-sided, acrylic tape with high UV resistance.

## Product Specifications

Roll Size	75mm x 25m
Colour	Black

## Product Applications

» Used to seal overlaps on Breather Membrane and Vapour Control Layers, along with joints and penetrations.

## Technical Data

Fire Classification (System Testing)	EN 13501-1	A2-s1,d0 with 0220FR Breather Membrane A2-s1,d0 with 0221FR Breather Membrane A2-s1,d0 with 0230FR AVCL Membrane B-s1,d0 with 0520FR Breather Membrane
Adhesive Carrier		LDPEco Film, Black, Reinforced with Scrim
Adhesive System		Acrylic Dispersion
Release Liner		Silicone-Coated Paper, Brown
Thickness, Without Liner	DIN EN 1942	0.30 – 0.33 mm
Peel Adhesion	DIN EN 1939**	≥ 35 N/25 mm
Elongation	DIN EN 14410	≥ 25 N/25 mm; 300 %
Temperature Resistance		-30 °C to +100 °C
Tack		Excellent
Condensation Water Resistance		High
Ageing Resistance		2 Years UV Resistance (Exposed)
Storage Temperature		10°C - 30°C
Installation Temperature		+5°C

### Associated Products

---

- » OBEX CORTEX 0824FR Double Sided Tape
- » OBEX CORTEX 0223FR Breather Membrane W1
- » OBEX CORTEX 0230FR VCL

### Additional Important Information

---

- » It is the responsibility of the user to test for compatibility.
- » OBEX Protection Ltd reserves the right to alter product specifications without prior notice, in line with its company policy of continuous development and improvement.
- » Consult the OBEX Technical Team for the latest version of the TDS, or with any other queries.
- » Product must be stored and used from correct temperature for optimum performance.