

0823FR UV Façade Tape

Technical Data Sheet

Version 01.01.02 Updated 25.04.25

Product Description

OBEX CORTEX 0823FR UV Façade Tape is a black, single-sided, acrylic tape with high UV resistance.

Product Specifications

Roll Size	75mm x 25m
Colour	Black

Product Applications

» Used to seal overlaps on Breather Membrane and Vapour Control Layers, along with joints and penetrations.

Technical Data

Adhesive Carrier		LDPEco Film, Black, Reinforced with Scrim
Adhesive System		Acrylic Dispersion
Release Liner		Silicone-Coated Paper, Brown
Thickness, Without Liner	DIN EN 1942	0.30 – 0.33 mm
Peel Adhesion	DIN EN 1939**	≥ 35 N/25 mm
Elongation	DIN EN 14410	≥ 25 N/25 mm; 300 %
Temperature Resistance		-30 °C to +100 °C
Tack		Excellent
Condensation Water Resistance		High
Ageing Resistance		2 Years UV Resistance (Exposed)
Storage Temperature		10°C - 30°C
Installation Temperature		+5℃





0823FR UV Façade Tape

TDSTechnical Data Sheet

Version 01.01.02 Updated 25.04.25

Associated Products

- » OBEX CORTEX 0824FR Double Sided Tape
- » OBEX CORTEX 0223FR Breather Membrane W1
- » OBEX CORTEX 0230FR VCL

Additional Important Information

- » It is the responsibility of the user to test for compatibility.
- » OBEX Protection Ltd reserves the right to alter product specifications without prior notice, in line with its company policy of continuous development and improvement.
- » Consult the OBEX Technical Team for the latest version of the TDS, or with any other queries.
- » Product must be stored and used from correct temperature for optimum performance.

