

0823FR UV Façade Tape

TDS Technical Data Sheet

Version 01.01.01 Updated 27.09.23

Product Description

OBEX CORTEX 0823FR UV Façade Tape is a black, singlesided, acrylic tape with high UV resistance.

Product Specifications

Roll Size	75mm x 25m
Colour	Black

Product Applications

» Used to seal overlaps on Breather Membrane and Vapour Control Layers, along with joints and penetrations.

Tec	hnicə	l Data

Adhesive Carrier		LDPEco Film, Black, Reinforced with Scrim
Adhesive System		Acrylic Dispersion
Release Liner		Silicone-Coated Paper, Brown
Thickness, Without Liner	DIN EN 1942	0.30 – 0.33 mm
Peel Adhesion	DIN EN 1939**	≥ 35 N/25 mm
Elongation	DIN EN 14410	≥ 25 N/25 mm; 300 %
Processing Temperature		+5 °C recommended, processable from -10 °C
Temperature Resistance		-30 °C to +100 °C
Tack		Excellent
Condensation Water Resistance		High
Ageing Resistance		2 Years UV Resistance (Exposed)



For more product information call us with your enquiry on **01905 337800**, email **info@obexuk.com** or visit www.obexuk.com OBEX Protection Ltd. Unit 12 Horn Hill Road, Nunnery Park, Nunnery Way, Worcester, WR4 0SX.



0823FR UV Façade Tape

TDS Technical Data Sheet

Version 01.01.01 Updated 27.09.23

Associated Products

- » OBEX CORTEX 0824FR Double Sided Tape
- » OBEX CORTEX 0223FR Breather Membrane W1
- » OBEX CORTEX 0230FR VCL

Additional Important Information

- » It is the responsibility of the user to test for compatibility.
- » OBEX Protection Ltd reserves the right to alter product specifications without prior notice, in line with its company policy of continuous development and improvement.
- » Consult the OBEX Technical Team for the latest version of the TDS, or with any other queries.

