

Product Description

OBEX CORTEX 0824FR Double-Sided Tape is a white, double-sided, acrylic tape with high bonding properties.

Product Specifications

Roll Size	50mm x 100m
Colour	White

Product Applications

» Used to bond Breather Membranes and Vapour Control Layers to the Façade.

Technical Data

Fire Classification (System Testing)	EN 13501-1	A2-s1,d0 with 0220FR Breather Membrane A2-s1,d0 with 0221FR Breather Membrane A2-s1,d0 with 0230FR AVCL Membrane B-s1,d0 with 0520FR Breather Membrane
Adhesive Carrier		Polyester Scrim
Adhesive System		Acrylic Dispersion
Release Liner		Silicone-Coated Filmic Liner, White
Thickness, Without Liner	DIN EN 1942	0.22 – 0.24 mm
Peel Adhesion	DIN EN 1939**	≥ 30 N/25 mm
Sheer Adhesion	DIN EN 14410	100g / 625mm ²
Temperature Resistance		-30 °C to +100 °C
Tack		Excellent
Condensation Water Resistance		High
Ageing Resistance		Very high
Storage Temperature		10°C - 30°C
Installation Temperature		+5°C

Associated Products

- » OBEX CORTEX 0824FR Double Sided Tape
- » OBEX CORTEX 0223FR Breather Membrane W1
- » OBEX CORTEX 0230FR VCL

Additional Important Information

- » It is the responsibility of the user to test for compatibility.
- » OBEX Protection Ltd reserves the right to alter product specifications without prior notice, in line with its company policy of continuous development and improvement.
- » Consult the OBEX Technical Team for the latest version of the TDS, or with any other queries.
- » Product must be stored and used from correct temperature for optimum performance.