

'nS Technical Data Sheet Version 01.01.02

Updated 13.06.25

Product Description

OBEX CORTEX S06000CPT is recommended for the protection of fibre carpets against dirt, dust and general light maintenance debris in medium traffic conditions.

Technical Data

Film backing	Polyethylene (LDPE)
Colour	Transparent
Adhesive type	Acrylic
Thickness average	62 micron
Adhesive strength	1.2 N/50mm

Storage and Use

The film must be stored in original packaging and applied at temperature <40°C

It must be used in a time lower than 9 months from the date of receipt

Application

This product should be removed within 30 – 45 days from the application date During the application the surfaces must be dry and free from dust, dirt, grease, oil or other foreign matter Surface must be vapour free. Allow all carpet adhesives to disperse to manufacturers recommendations We recommend the use of an application dispenser details available For inside use only NOT FOR USE ON HARD SURFACES, WOOD, CERAMIC, MARBLE etc

Disclaimer

Applications

Carpeted floors

Synthetic carpet floor covering

Natural carpet floor covering

This film is recommended for the protection of carpeted flooring only

We suggest to our customers an evaluation trial to confirm the suitability use of this product Obex Protection is not responsible for a misuse of this product, nor for the consequences of an improper application.

All information in this datasheet is given in good faith on the basis of practical experience



For more product information call us with your enquiry on **01905 337800**, email **info@obexuk.com** or visit **www.obexuk.com OBEX Protection Ltd.** Unit 5, Indurent Park, Norton Rd, Broomhall, Worcester WR5 2QR